CIVIC THEATRE

TECHNICAL SPECIFICATION FOR LOOSE END STUDIO.

AUDITORIUM

Seating capacity 69.

Larger Performance area (remove front row) capacity is 59.

Seating blocks located on 3 sides of performance area.

Performance Area

Floor is solid concrete. Fixing to floor is not possible.

Stage depth 4270mm. Stage width 7320mm. Grid height 2920mm.

LIGHTING

Control Desk.

1 No. E.T.C. Express 125 lighting console with riggers remote.

Dimmers

24 way ZERO 88 Chilli Dimmer rack.

19 circuits distributed through out grid.

5 circuits available on stage left wall.

Lanterns

10 x Strand Quartet Profile 650W.

10 x Strand Quartet Fresnel 650W.

6 x Selecon Fresnel 650W.

5 x Selecon 12/28 Profile 600w.

SOUND

Desk

1 No. Yamaha EMX 5014c Desk.

Speakers

2 No. D.A.S. D8 150 W Speakers.

Playback

2 No. Sony Mini Disc players.

1 No. Denon C.D. Player.

STAGE EQUIPMENT

Additional equipment such as stage braces and weights can be obtained from the main auditorium stock when available.

<u>DRESSINGROOMS</u>

There are 2 small dressingrooms, Toilet and Shower backstage.